



## TURNOUT GRINDING MACHINE LRGM 1-6/ AM65



L & S Luddeneit und Scherf GmbH  
Wimmlerstraße 25  
D-07806 Neustadt an der Orla  
GERMANY

www.l-und-s.de  
Tel.: +49-36481-5645-0  
Fax: +49-36481-5645-19



The LRG 1-6/ AM65 is a plain track and a turnout grinding machine for the machining of the rail head which composes except the grinding unit also a generator so that no power cables has to be installed along the working site. The grinder can be easily railed in and out with a ramp of a rail vehicle or by crane.

The grinding machine has 6 grinding spindles with independent angular adjustment. They are driven by 7,5 to 15 kW frequency controlled electrical motors. The machine can be equipped with an integrated laser measurement system for the analysis of the transverse and longitudinal rail head profile.

The LRG 1-6/ AM65 grinder can be used for removing of the rolling skin, the elimination of rail corrugations (grooves) and short waves on the rail head as well as for the re-profiling of the rail head. The grinder is efficient for grinding of turnouts, machining of railroad crossings, grinding of welding, machining of taper rail and for winning the transverse and longitudinal target profiles in short rail sections.

Rail-in time: approx. 10 minutes

Rail-out time: approx. 5 minutes

# Technical data of the rail grinder LRGM 1-6 /AM65

Length .....	6.750 mm
Breadth .....	2.300 mm
Hight .....	max. 2.400 mm
Weight .....	3.150 kg + 2.950 kg
Gauge .....	1000 to 1524 mm
Minimum curve radius .....	travelling: 15 m grinding: 20 m
Numbers of grinding motors .....	6
Power of grinding motors .....	7,5 kW to 15 kW per motor
Speed of cup stones .....	max. 6000 rpm, infinitely variable by integrated frequency converter
Max. grinding angle .....	-15° outside of the rail (field side) +70° inside of the rail (gauge side)
Operation .....	- computer monitored grinding process - grinding in both directions - fixed and adjustable grinding programs
Modification of grinding angles .....	electro mechanical control
Feeding mechanism for grinding stone .....	electro mechanical control
Horizontal grinding stone adjusting .....	electro mechanical control
Rail travel speed .....	10 km/h
Grinding speed .....	1,0 to 3,0 km/h
Maximum slope .....	70 ‰
Vacuum power for grinding dust .....	2 x 0,55 kW; volumetric flow rate 375 m <sup>3</sup> /h
Power of drive unit on rail .....	3,5 kW frequency converted 3-phase current motor
Electrical connection .....	400 V 32 A CEE connection; further connections of electrical machines are possible on the control board of the controlling system
Power supply .....	LRAM 65 generating set; 65 kW power output, 74 dBA
Lighting of working place .....	4 x 24V/70W halogen headlamp
Option .....	- integrated laser measurement system with storage function and real-time analysis - air-conditioned operator cabine - water tank (120l) with spray and cleaning system - particle-emission filter for exhaust gases
Protections .....	- spark shields

## DEVELOPMENT – DESIGN – MANUFACTURING – SALE – SERVICE

L&S Luddeneit und Scherf GmbH  
Wimmlerstraße 25  
D- 07806 Neustadt an der Orla - Germany

Tel.: +49 (0) 36481-5645-0  
Fax: +49 (0) 36481-5645-19

LUDDENEIT UND SCHERF GMBH

