



RAIL GRINDING MACHINE RRGM 0-16

L & S Luddeneit und Scherf GmbH
Wimmlerstraße 25
D-07806 Neustadt an der Orla
GERMANY

www.l-und-s.de

Tel.: +49-36481-5645-0
Fax: +49-36481-5645-19



The rail grinder RRGM 0-16 is a rail-road going machine. The machine has 16 grinding motors with independent angular adjustment. They are driven by frequency-controlled electrical 7,5 kW motors. The computer monitored grinding process is controlled with touch pad by the operator inside of the cabin.

The rail grinder can be used for removing of rolling skin, the elimination of rail corrugations (grooves) and short waves on the rail head as well as for reprofiling of the rail head.

The grinder RRGM 0-16 is efficient for working in the open and closed scopes of long rail sections for winning the transverse and longitudinal target profiles.

| | |
|---------------------------|-------------------|
| Insertion time on rail: | approx. 8 minutes |
| Discharging time of rail: | approx. 4 minutes |

LUDDENEIT UND SCHERF GMBH

Technical data of the rail grinder RRGM 0-16

| | |
|--|---|
| Length | 15.920 mm |
| Breadth | 2.300 mm |
| Hight | 3.200 mm |
| Weight | 26 t |
| Gauge | 1000 to 1524 mm |
| Axle load | max. 6,5 t |
| Minimum curve radius | Travelling: R25 m Grinding: R35 m |
| Numbers of grinding motors | 16 |
| Power of grinding motors | 7,5 kW per motor |
| Speed of cup stones | max. 5850 rpm, infinitely variable by integrated frequency converter |
| Max. grinding angle | -25° outside of the rail (field side) +70° inside of the rail (gauge side) |
| Operation | - computer monitored grinding process - availability of 100 grinding programs - grinding in both directions |
| Modification of grinding angles | electro mechanical control |
| Feeding mechanism for grinding stone | electro mechanical control |
| Horizontal grinding stone adjusting | electro mechanical control |
| Road travel speed | 80 km/h |
| Rail travel speed | 40 km/h |
| Grinding speed | max. 1,5 to 3,5 km/h |
| Maximum slope | 70 ‰ |
| Vacuum power for grinding dust | 4 x 4,5 kW volumetric flow rate 15.000 m ³ /h |
| Water tank | 600 litres |
| Protections | - vertical adjustable spark shields - particle-emission filter for exhaust gases |
| Approvals | - EBA approval acc. European standards - approval for grinding on german rail ways of the DB Netz AG |

DEVELOPMENT - DESIGN - MANUFACTURING - SALE - SERVICE

L&S Luddeneit und Scherf GmbH
Wimmlerstraße 25
D- 07806 Neustadt an der Orla - Germany

Tel.: +49 (0) 36481-5645-0
Fax: +49 (0) 36481-5645-19

